



Circuit	Dimensions(mm)	
	A	B
02	2.50	7.50
03	5.00	10.00
04	7.50	12.50
05	10.00	15.00
06	12.50	17.50
07	15.00	20.00
08	17.50	22.50
09	20.00	25.00
10	22.50	27.50
11	25.00	30.00
12	27.50	32.50
13	30.00	35.00
14	32.50	37.50
15	35.00	40.00
16	37.50	42.50
17	40.00	45.00
18	42.50	47.50
19	45.00	50.00
20	47.50	52.50

Material:
Housing:PA66(UL94V-0),White
Contacts:Brass Tin

Electrical Characteristics:
1.Poles: 2 to 20P
2.Current rating: 3.0A
3.Voltage rating: 250V
4.Temperature range: -25°C to +85°C
5.Contact resistance: $\leq 10m\Omega$
6.Insulation resistance: $\geq 1000M\Omega$
7.Withstand voltage: 1000V AC/minute
8.Applicable wire: AWG #30 to #22
9.Applicable PC board thickness: 1.6mm

Order Information
L-KLS1-2.50-XX-R

- Type:R=Right Male pin
- PIN Number: 02~20Pin
- Pitch: 2.50=2.50mm
- Series No.
- RoHS

GENERAL TOLERANCE	X	±0.50	PROJECTION		Description:	2.50mm Pitch XH Type
	.X	±0.25				Wire To Board Connector
	.XX	±0.10				
ANGLE TOLERANCE	X	±5°	Draw by:	Jenny	KLS P/N:	L-KLS1-2.50-XX-R
	.X	±3°	Check by:			NingBo KLS ELECTRONIC CO.,LTD.
	.XX	±2°	Date	2018-03-01		
			SHEET	1 OF 1		