




Package	Part No. FYL-	Chip		Lens Appearance	Pulse Rate(Hz) VDD=5V(Hz)			Luminous Intensity IF=50mA(mcd)		Viewing Angle 2 θ 1/2 (deg)	Drawing No.
		Material/Emitted Color	Peak Wave Length λ p (nm)		Min.	Typ.	Max.	Min.	Typ.		
T-1 Standard 1.0" Lead φ3	3014LRD-B	GaAlAs/DHSuper Red	660	Red diffused	2.0	2.4	2.8	15.0	30	60	L-022
	3014ED-B	GaAsP/GaP Orange	635	Red diffused				8.0	20		
	3014GD-B	GaP/GaP Green	570	Green diffused				8.0	20		
	3014YD-B	GaAsP/GaP Yellow	585	Yellow diffused				6.0	15		
T-1 3/4 Standard 1.0" Lead φ5	5013LRD-B	GaAlAs/DHSuper Red	660	Red diffused	2.0	2.4	2.8	20.0	50	60	L-023
	5013ED-B	GaAsP/GaP Orange	635	Red diffused				12.0	30		
	5013GD-B	GaP/GaP Green	570	Green diffused				12.0	30		
	5013YD-B	GaAsP/GaP Yellow	585	Yellow diffused				10.0	25		



L-022 FYL-3014xx Series	L-023 FYL-5013xx Series
----------------------------	----------------------------

